

9kVA Silent Diesel Generator Set

HTX-G14K-S is a silent (canopied) diesel generator set: 9 kVA (single-phase) / 11.2 kVA (three-phase) prime power at 50 Hz. HTX-AE1105 engine, 74 dB(A) at 7 m, 15 L fuel tank.

SPECIFICATIONS

Prime power	9 kVA (single) / 11.2 kVA (three)
Standby power	9.9 kVA (single) / 12.3 kVA (three)
Rated voltage	115/230 (single) / 400/230 (three) V
Phase / Frequency	Single-phase / Three-phase, 50Hz, 3000rpm
Power factor	1.0 (single) / 0.8 (three)
Engine model	HTX-AE1105
Engine bore x stroke	105 x 88 mm
Engine displacement	0.762 L
Compression ratio	19:1
Engine rated power	11.7 kW
Fuel consumption	280 g/kW.h
Oil capacity	2.1 L
Start mode	Electric start
Battery capacity	12V-36Ah
Frame type	Sound-attenuated canopy
Fuel tank capacity	15 L
Net weight	256 kg
Overall dimension	1180*640*865 mm
Alternator type	Copper-wound with AVR voltage stabilizer
Noise level @ 7 m	74 dB(A)



KEY FEATURES

- Single-phase 9kVA or three-phase 11.2kVA from the same set
- Copper-wound alternator with AVR voltage stabilizer
- HTX-AE1105 single-cylinder air-cooled engine, 11.7kW
- Sound-attenuated canopy, 74 dB(A) at 7 m
- 12V electric start

APPLICATIONS

Construction · Mining · Emergency Power · Industrial · Telecom Base Station

ORDERING & EXPORT

Warranty	12 months / 1,000 hours (whichever first) — manufacturing defects, replacement parts
Packaging	Confirmed with each order