

10.5kVA Twin-Cylinder Silent Diesel Generator Set

HTX-G14K-S2P is a silent (canopied) diesel generator set: 10.5 kVA (single-phase) / 13.1 kVA (three-phase) prime power at 50 Hz, 11.6 kVA (single-phase) / 14.5 kVA (three-phase) at 60 Hz. HTX-AE292 engine, 74 dB(A) at 7 m, 28 L fuel tank.

SPECIFICATIONS

Prime power	10.5 kVA (single) / 13.1 kVA (three)
Prime power (60 Hz)	11.6 kVA (single) / 14.5 kVA (three)
Standby power	11.6 kVA (single) / 14.5 kVA (three)
Standby power (60 Hz)	12.7 kVA (single) / 15.8 kVA (three)
Rated voltage	115/230 (single) / 400/230 (three) V
Rated voltage (60 Hz)	120/240 (single) / 416/240 (three) V
Phase / Frequency	Single-phase / Three-phase, 50/60Hz, 3000/3600rpm
Power factor	1.0 (single) / 0.8 (three)
Engine model	HTX-AE292
Engine bore x stroke	2-92 x 75 mm
Engine displacement	0.997 L
Compression ratio	19:1
Engine rated power	13.53 kW
Fuel tank capacity	28 L
Fuel consumption	240 g/kW.h
Oil capacity	2.8 L
Start mode	Electric start
Battery capacity	12V-36Ah
Frame type	35mm square tube, silent enclosure
Net weight	307 kg
Overall dimension	1300*670*895 mm
Alternator type	Copper-wound with AVR voltage stabilizer
Noise level @ 7 m	74 dB(A)



KEY FEATURES

- Twin-cylinder engine for smooth, powerful operation
- Sound-attenuated enclosure with anti-corrosion canopy
- Copper-wound alternator with AVR voltage stabilizer
- 2-92x75mm borexstroke, 0.997L displacement, 13.53kW engine output
- 28L large fuel tank for extended runtime

APPLICATIONS

Construction · Mining · Industrial · Large Events · Emergency Power

ORDERING & EXPORT

Warranty	12 months / 1,000 hours (whichever first) — manufacturing defects, replacement parts
Packaging	Confirmed with each order