

## 11kVA Silent Diesel Generator Set

HTX-G18K-S is a silent (canopied) diesel generator set: 11 kVA (single-phase) / 13.8 kVA (three-phase) prime power at 50 Hz, 12.1 kVA (single-phase) / 15.1 kVA (three-phase) at 60 Hz. HTX-AE292 engine, 74 dB(A) at 7 m, 28 L fuel tank.

### SPECIFICATIONS

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| Prime power           | 11 kVA (single) / 13.8 kVA (three)                |
| Prime power (60 Hz)   | 12.1 kVA (single) / 15.1 kVA (three)              |
| Standby power         | 12.1 kVA (single) / 15.1 kVA (three)              |
| Standby power (60 Hz) | 13.3 kVA (single) / 16.6 kVA (three)              |
| Rated voltage         | 115/230 (single) / 400/230 (three) V              |
| Rated voltage (60 Hz) | 120/240 (single) / 416/240 (three) V              |
| Phase / Frequency     | Single-phase / Three-phase, 50/60Hz, 3000/3600rpm |
| Power factor          | 1.0 (single) / 0.8 (three)                        |
| Engine model          | HTX-AE292                                         |
| Engine bore x stroke  | 2-92 x 75 mm                                      |
| Engine displacement   | 0.997 L                                           |
| Oil capacity          | 2.8 L                                             |
| Frame type            | Sound-attenuated canopy                           |
| Fuel tank capacity    | 28 L                                              |
| Net weight            | 307 kg                                            |
| Overall dimension     | 1300*670*895 mm                                   |
| Alternator type       | Copper-wound with AVR voltage stabilizer          |
| Noise level @ 7 m     | 74 dB(A)                                          |



### KEY FEATURES

- Single-phase 11kVA or three-phase 13.8kVA from the same set
- Copper-wound alternator with AVR voltage stabilizer
- Sound-attenuated canopy, 74 dB(A) at 7 m
- 50 Hz and 60 Hz versions
- 12V electric start

### APPLICATIONS

Construction · Mining · Emergency Power · Industrial · Telecom Base Station

### ORDERING & EXPORT

|           |                                                                                      |
|-----------|--------------------------------------------------------------------------------------|
| Warranty  | 12 months / 1,000 hours (whichever first) — manufacturing defects, replacement parts |
| Packaging | Confirmed with each order                                                            |