

12kVA Open Frame Diesel Generator Set

HTX-G18K-XE is an open-frame diesel generator set: 12 kVA (single-phase) / 15 kVA (three-phase) prime power at 50 Hz, 13.2 kVA (single-phase) / 16.5 kVA (three-phase) at 60 Hz. HTX-AE292 engine, 80 dB(A) at 7 m, 30 L fuel tank.

SPECIFICATIONS

Prime power	12 kVA (single) / 15 kVA (three)
Prime power (60 Hz)	13.2 kVA (single) / 16.5 kVA (three)
Standby power	13.2 kVA (single) / 16.5 kVA (three)
Standby power (60 Hz)	14.5 kVA (single) / 18.1 kVA (three)
Rated voltage	115/230 (single) / 400/230 (three) V
Rated voltage (60 Hz)	120/240 (single) / 416/240 (three) V
Phase / Frequency	Single-phase / Three-phase, 50/60Hz, 3000/3600rpm
Power factor	1.0 (single) / 0.8 (three)
Engine model	HTX-AE292
Engine bore x stroke	2-92 x 75 mm
Engine displacement	0.997 L
Oil capacity	2.8 L
Fuel tank capacity	30 L
Net weight	219 kg
Overall dimension	940*670*905 mm
Alternator type	Copper-wound with AVR voltage stabilizer
Noise level @ 7 m	80 dB(A)



KEY FEATURES

- Single-phase 12kVA or three-phase 15kVA from the same set
- Copper-wound alternator with AVR voltage stabilizer
- 50 Hz and 60 Hz versions
- 12V electric start

APPLICATIONS

Construction · Mining · Industrial · Emergency Power · Large Events

ORDERING & EXPORT

Warranty	12 months / 1,000 hours (whichever first) — manufacturing defects, replacement parts
Packaging	Confirmed with each order