

200A Diesel Welding Generator Set, HTX-AE192 Engine

HTX-GW220E is a diesel welding generator: 200 A welding current, 1.6-4.0 mm electrodes, 60% duty cycle, plus 5 kVA single-phase auxiliary power at 50 Hz. HTX-AE192 engine, 12.5 L fuel tank.

SPECIFICATIONS

Generator output	5 kVA
Generator output (60 Hz)	5.5 kVA
Rated welding current	200 A
Welding duty cycle	60%
Welding electrode diameter	1.6-4.0 mm
Rated voltage	230 V
Rated voltage (60 Hz)	240 V
Phase / Frequency	Single-phase, 50/60Hz, 3000/3600rpm
Engine model	HTX-AE192
Engine bore x stroke	92 x 75 mm
Engine displacement	0.499 L
Oil capacity	1.65 L
Fuel tank capacity	12.5 L
Fuel consumption (100% load)	2.39 L/h
Fuel consumption (75% load)	1.82 L/h
Net weight	125 kg
Overall dimension	745*515*730 mm



KEY FEATURES

- Welding current 200A
- Electrodes 1.6-4.0mm, 60% duty cycle
- 5kVA single-phase power for tools and lights
- HTX-AE192 air-cooled diesel engine
- 12.5L fuel tank

APPLICATIONS

Construction · Field Welding · Pipeline Repair · Mining · Agriculture

ORDERING & EXPORT

Warranty	12 months / 1,000 hours (whichever first) — manufacturing defects, replacement parts
Packaging	Confirmed with each order