

30HP Single-Cylinder Water Cooled Diesel Engine

HTX-WE32 is a single-cylinder water-cooled diesel engine: 22 kW (29.92 hp) rated at 2200 rpm. 1.659 L displacement, net weight 215 kg.

SPECIFICATIONS

Rated speed	2200 rpm
Rated power	22 / 29.92hp kW / hp
Max power	24.20 / 32.91hp kW / hp
Bore x Stroke	130 x 125 mm
Displacement	1.659 L
Compression ratio	17:1
Max torque	109.83 @ 1650rpm N.m
Oil capacity	3.1 L
Start mode	Hand start or electric start
Net weight	215 kg
Overall dimension	1052*544*808 mm



KEY FEATURES

- Direct injection combustion system for low fuel consumption
- Maximum torque 109.83 N.m at 1650rpm with strong load handling
- High compression ratio 17:1 for easy low-temperature starting
- Robust water-cooling system for sustained heavy-duty operation
- Largest displacement in the WE series (1.659L) for maximum output

APPLICATIONS

Agriculture · Construction · Generator Set · Water Pump · Mining

ORDERING & EXPORT

Warranty	12 months / 1,000 hours (whichever first) — manufacturing defects, replacement parts
Packaging	Confirmed with each order